







Smooth roll out axle extension on 25' model.

10' Tower (ideal for Cherries, Apples & Citrus)

Push Button Free Wheeling Hub for towing or manual positioning.



## PRUNE-RITE SPECIFICATIONS

PR120 (10'), PR180 (15'), PR240 (20'), PR300 (25') all with Cruiser Speed

SPECIFICATIONS	PR120	PR180	PR240	PR300
Platform height in feet	10'	15'	20'	25'
Engine (diesel)	Kubota D-1105, 25 hp	•	•	•
Cruiser Speed Joystick	Joystick hydraulic - 2 speed electri	<b>•</b>	•	•
Throttle (operator platform)	Electric solenoid	•	•	•
Tow Capacity	Highway towable	•	•	•
Tow Package	Tongue, jack	•	•	•
Hydraulic Pump	Dual	•	•	•
Boom Lift Control	Electric hydraulic	•	•	•
Turning Radius	<b>以及是一种企业的</b>	9.5'	9.5'	10.0'
Length (in inches)	175"	205"	215"	280"
Width (in inches) fixed	72"	96"	117"	
Width (in inches) wheels retracted				117"
Width (in inches) wheels extended				153"
Weight (in pounds)	1400 lbs	2150 lbs	2350 lbs	2950 lbs
Stabilizer Bar Bearings	2/non-serviceable bearings	•	•	•
Main Boom Pivot Bearings	2/urethane bearings	•	•	•
Cage Pivot Bottom Bearings	2/urethane bearings	•	•	•
Boom Cylinder Pivots	2/urethane bearings	•	•	• •
Caster Wheel Pivot	Sealed timken bearings	•	•	•
Frame	Uniwelded tubular	•	•	•
Caster Tires	11L x 15	•	•	•
Drive Tires	31 x 15.50 - 15	•	•	•
Boom	Tubular with top bridge	•	•	•
Fuel Capacity	6.0 gal (integrated in frame) 2!	5.0 gal Poly	Tank •	•
Hydraulic Oil Capacity	14.0 gal (integrated in frame)	14.0 gal	14.0 gal	14.0 gal
Hour Meter	Engine oil pressure activated	•	• •	•
OPTIONS:		9		
Partial Cage Enclosure	Front of cage enclosed	•	•	•
Full Cage Enclosure	3 sides enclosed & door	•	•	•
Oil Cooler	Mounted in front of radiator	•	•	•
Cage heater	Oil cooler in cage with electric fan	•	•	•
Hub Lockout Adaptors	Push-button type	•	•	•